

NOTE: Fits most bikes with front or side top triple clamp pinch bolts regardless of handlebar size or type.

Fitting Instructions

Remove the original, top triple clamp pinch bolts. Fit the upright post (1), with the long flange bolts (5), to the top triple clamp (2 or 3).

Do not tighten at this stage.

The upright post (1) can be adjusted up and down for height variation.

Fit the Barkbusters handguard as per instructions on the packaging. Now fit the connecting arm between the Barkbusters alloy bar and the upright post (1) with the bolts supplied. (See diagram.)
Diagram shows left side connecting arm with undercut towards the front.


Position all parts so they align with each other, and then tighten all bolts.

The flange bolt (4) that holds the connecting arm to the upright post should be tightened last.

Important: Use a mild thread locking compound on all bolts.


Note: *If this triple clamp mounting is fitted to a Honda XR 250/400/600 you will need to purchase 4 x 65mm long bolts to use in place of the 4 x 60mm bolts supplied. This is to ensure you have a minimum of 12mm thread engagement.*

1 Triple Clamp Post




PN: TCP
Pcs. 2

2 Triple Clamp Arm - Left



PN: TCCA-L
Pcs. 1

3 Triple Clamp Arm - Right



PN: TCCA-R
Pcs. 1

4 Bolt



PN: M8x25FB10ZP
Pcs. 4

5 Bolt



PN: M8x60FHB10ZP
Pcs. 4

6 Flat Head Bolt 45mm



PN: M8x45FHCSZP
Pcs. 2

7 Collar



PN: BBEC5m
Pcs. 2

8 Expander



PN: BBE14A
Pcs. 2

9 Taper Nut



PN: NUT12
Pcs. 2

10 Collet



PN: COLLET14-18
Pcs. 2

CAUTION:

Installation of the handguard is safety-relevant work and can be complicated. We recommend the installation be performed by a motorcycle service technician. Rideworx accepts no liability for damages caused by improper mounting. All screws, bolts and nuts, including all replacement hardware provided by Rideworx, should be tightened to the torque specified in the table. After the first 50km of riding check all screws, bolts and nuts are tightened to the correct torque. We recommend a medium strength liquid thread lock product on all fasteners.

WARNING:

It is important there is a working clearance (approx 3mm) between the throttle grip end and the handguard to ensure a free closing throttle. Check operation of all handlebar controls, specifically the throttle, front brake, kill switch and clutch to ensure they are operating correctly and are in accordance with the OEM specifications. Do not ride the motorcycle if any controls are not operating correctly. Check periodically that all bolts are tight.

Recommended Torque Settings	
M6	10 Nm (7.4 lbf ft)
M8	20 Nm (14.8 lbf ft)



Phone: +61 (0)2 4271 8244
Email: info@barkbusters.net
Web: www.barkbusters.net



Disclaimer:
Rideworx inspects all products prior to packaging and strives toward improving its products. Our guarantee is limited to the replacement of defective products. This limited guarantee is in lieu of all other guarantees or warranties implied or expressed. Buyer assumes all risk for any and all damage caused to him/herself, a third party and/or property by virtue of failure of this product. We make no warranty as to products distributed by Rideworx, expressed or implied from our suppliers or third party vendors. This includes, without limitation, any warranties or merchantability and fitness for a particular purpose. All products are offered and designed for use with standard machines. Rideworx makes no claims as to the products effectiveness on modified machines. Rideworx is the sole determiner of abuse, misuse, installation errors and modifications. We assume no liability for any errors in listings, specifications, part numbers, prices or model applications. We reserve the right to change specifications, product descriptions, product quality, pricing and application at any time without notice and without further obligation. These handguards are not designed to prevent injury in the event of an accident or crash. Ensure all controls are free of the handguards each time you ride. Failure to follow the instructions or heed this warning could lead to loss of control of your motorcycle and/or accident, injury or death. By installing and/or using a Rideworx product, you hereby accept and understand these stated terms and conditions and have followed all instructional steps.